

# **ENVIRONMENTAL PRODUCT DECLARATION**

in accordance with ISO 14025, ISO 21930 and EN 15804

Owner of the declaration:	Fora Form AS
Program operator:	The Norwegian EPD Foundation
Publisher:	The Norwegian EPD Foundation
Declaration number:	NEPD-3117-1773-EN
Registration number:	NEPD-3117-1773-EN
ECO Platform reference number:	-
Issue date:	17.09.2021
Valid to:	17.09.2026

# Clint stackable - sled base / high backrest

Fora Form AS

www.epd-norge.no



### **General information**

Product:

Clint stackable - sled base / high backrest

Owner of the declaration:

Fora Form AS Contact person: Kåre Sætre Phone: +47 700 46 000 e-mail: info@foraform.com

Program operator:

The Norwegian EPD Foundation Pb. 5250 Majorstuen, 0303 Oslo Phone: +47 23 08 80 00 e-mail: post@epd-norge.no

Manufacturer:

Fora Form AS

**Declaration number:** 

NEPD-3117-1773-EN

Place of production:

Fora Form AS Mosflatevegen 6154 Ørsta Norway

**ECO Platform reference number:** 

Management system:

NS-EN ISO 14001: 2015 No. 800406. NS-EN ISO 9001: 2015 No. 901268. NS-EN ISO 45001: 2018 No 907167.

This declaration is based on Product Category Rules:

CEN Standard EN 15804:2012+A1:2013 serves as core PCR NPCR 026:2018 Part B for furniture

Organisation no:

986 581 421

Statement of liability:

The owner of the declaration shall be liable for the underlying information and evidence. EPD Norway shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

Issue date: 17.09.2021

Valid to: 17.09.2026

**Declared unit:** 

1 Pcs Clint stackable - sled base / high backrest

Year of study:

**Declared unit with option:** 

2021

beciared unit with option.

Comparability:

 $\ensuremath{\mathsf{EPDs}}$  from programmes other than the Norwegian  $\ensuremath{\mathsf{EPD}}$  Foundation may not be comparable

Functional unit:

A1,A2,A3,A4

Functional unit whitout cardboard packaging is tot. 10,3kg.

Development and verification of EPD:

The declaration has been developed and verified using EPD tool lca.tools ver EPD2020.11, developed by LCA.no AS. The EPD tool is integrated into the company's environmental management system, and has been approved by EPD-Norway

General information on verification of EPD from EPD tools:

Independent verification of data, other environmental information and the declaration according to ISO 14025:2010, § 8.1.3 and § 8.1.4. Individual third party verification of each EPD is not required when the EPD tool is i) integrated into the company's environmental management system, ii) the procedures for use of the EPD tool are approved by EPDNorway, and iii) the proccess is reviewed annualy. See Appendix G of EPD-Norway's General Programme Instructions for further information on EPD tools.

Developer of EPD:

Kåre Sætre

Reviewer of company-specific input data and EPD:

Katrine Østgaard

Verification of EPD tool:

Independent third party verification of the EPD tool, background data and test-EPD in accordance with EPDNorway's procedures and guidelines for verification and approval of EPD tools.

Approved:

Sign

Erik Svanes, Norsus AS

(no signature required)

Håkon Hauan, CEO EPD-Norge

Key environmental indicators	Unit	Cradle to gate A1 - A3
Global warming	kg CO2 eqv	37,64
Total energy use	MJ	793,03
Amount of recycled materials	%	8,28

### **Product**

#### Market:

Worldwide

#### **Product description:**

Clint is a classic Conference Chair With a elegant Nordic design. The classic design award winning design will last a Lifetime. The Chair Family is avaliable in a formal high back Version and a lower back, with a sleek steel armrest or solid armrests ready for longer Meetings. A classic nordic design to last a lifetime The simplistic design allows the ability to customize to your organizations idenity

#### **Product specification**

Dimensions Width: 55 cm Height: 108 cm Depth: 58 cm Seat height: 46,5 cm

Furniture test approved

EN-16139:2013

#### **Technical data:**

Weight 10,3

Reference service life, product

15 years

Reference service life, building

Materials	kg	%	Recycled share in material (kg)	Recycled share in material (%)
Metal - Steel	4,10	36,28	0,82	20,00
Textile - Polyester (PE)	1,00	8,85	0,00	0,00
Plastic - Polyurethane (PUR)	1,70	15,04	0,00	0,00
Plastic - Polyoxymethylene (POM)	0,10	0,88	0,05	50,00
Wood - Plywood	3,40	30,09	0,00	0,00
Cardboard	1,00	8,85	0,76	76,30

# LCA: Calculation rules

#### **Declared unit:**

1 Pcs Clint stackable - sled base / high backrest

## Cut-off criteria:

All major raw materials and all the essential energy is included. The production processes for raw materials and energy flows with very small amounts (less than 1%) are not included. These cut-off criteria do not apply for hazardous materials and substances.

#### Allocation:


The allocation is made in accordance with the provisions of EN 15804. Effects of primary production of recycled materials is allocated to the main product in which the material was used. The recycling process and transportation of the material is allocated to this analysis.

#### Data quality:

Specific data for the product composition are provided by the manufacturer. They represent the production of the declared product and were collected for EPD development in the year of study. Background data is based on registered EPDs according to EN 15804, Ostfold Research databases, ecoinvent and other LCA databases. The data quality of the raw materials in A1 is presented in the table below.

Materials	Source	Data quality	Year
Plastic - Polyurethane (PUR)	ecoinvent 3.4	Database	2015
Metal - Steel	ecoinvent 3.3	Database	2016
Cardboard	ecoinvent 3.4	Database	2017
Metal coating - Powder coating on steel	ecoinvent 3.4	Database	2017
Plastic - Polyoxymethylene (POM)	ecoinvent 3.4	Database	2017
Process	ecoinvent 3.4	Database	2017
Textile - Polyester (PE)	ecoinvent 3.4	Database	2017
Wood - Plywood	ecoinvent 3.4	Database	2017

#### System boundary:



#### Additional technical information:

We want you to enjoy your furniture for many years to come. If you follow our advice in this Quality and Maintenance Manual you contribute to prolonged life of your furniture. We only use environmentally friendly materials and processes in our manufacturing unit in Ørsta Norway. Our goal is to manufacture furniture that can last for generations. All furniture made by Fora Form are made of FSC certified wood, manufactured according to ISO 14001, and has an EPD on all products. This ensures sustainability and a "cradle to cradle" philosophy. We actively work to reduce waste. All packing materials and waste are being recycled according to Norsk Gjenvinning.

Norwegian and Swedish Møbelfakta are accredited test facilities where furniture quality, strength, durability, flammability, safety, emissions and materials are tested and documented. A piece of furniture, which lives up to the three areas of requirements of Møbelfakta, has undergone extensive testing, is produced according to ethical guidelines and has been approved according to environmental requirements. Møbelfakta is a guarantee of high quality products. Almost all of Fora Forms collection is Møbelfakta approved.

Fora Form are ISO 9001 quality management, ISO 14001 environmental management and ISO 45001 occupational health and safety management certified. Sustainability is important for Fora Form.

We continuously work to sort and reduce our waste, and collaborate with Norsk Gjenvinning and Grønt Punkt (Green Dot Norway plc) regarding recycling of used packing materials. All wood is FSC certified.

Our manufacturing unit in Ørsta use electricity that is 100% originated from renewable sources.

Transportation to an average customer in Oslo is 540 km (A4: average European lorry > 32 tonnes)

Value

# The following information describe the scenarios in the different modules of the EPD.

The following information describe the scenarios in the different modules of the EPD.

# Transport from production place to user (A4)

Туре	Capacity utilisation (incl. return) %	Type of vehicle	Distance km	Fuel/Energy consumption	Unit	Value (I/t)
Truck	38,8 %	Truck, 16-32 tonnes, EURO 5	50	0,044606	l/tkm	2,23
Railway					l/tkm	
Boat					l/tkm	
Other Transportation					l/tkm	

Use (B1)

Assembly (A5)			
---------------	--	--	--

	Unit	Value
Auxiliary	kg	
Water consumption	m <sup>3</sup>	
Electricity consumption	kWh	
Other energy carriers	MJ	
Material loss	kg	
Output materials fr ste treatment	kg	
Dust in the air	kg	
VOC emissions	kg	

_		
Replacement	(B4)/Refurbishment (B5)	

	Unit	Value
Maintenance cycle*	SCO	
Auxiliary	ana.	
Other resources	4/10	)
Water consumption	Scenario	3. 9k
Electricity consumption	kWh	.16
Other energy carriers	MJ	
Material loss	kg	
VOC emissions	kg	

	Unit	Value
Replacement cycle*		
Electricity consumption	kWh	
Replacement of worn parts		
* Described above if relevant		

#### Described above if relevant

# Operational energy (B6) and water consumption (B7)

	Unit	Value
Water consumption	m <sup>3</sup>	
Electricity consumption	kWh	
Other energy carriers	MJ	
Power output of equipment	KW	

* Described above if relevant		
) n		
'A-		
1/2/		
74		
are		
End of Life (C1)		
End of Life (C1, C		
1701	Unit	Value
Hazardous waste disposed	kg	
Collected as mixed construction was	kg	
Reuse	kg	
End of Life (C1, C ) Hazardous waste disposed Collected as mixed construction ws. Reuse Recycling Energy recovery	_	
Energy recovery	_	
To landfill		_
	kg	

#### Transport to waste processing (C2)

Туре	Capacity utilisation (incl. return) %	Type of vehicle	Distance km	Fuel/Energy consumption	Unit	Value (I/t)
Truck					I/tkm	
Railway					I/tkm	
Boat					I/tkm	
Other Transportation					I/tkm	

# **LCA: Results**

The LCA results are presented below for the declared unit defined on page 2 of the EPD document.

# System boundaries (X=included, MND=module not declared, MNR=module not relevant)

Pr	oduct sta	age	instal	uction lation ige			l	Jser stag	e			End of life stage			•	Beyond the system bondaries
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De- construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery- Recycling- potential
A1	A2	A3	A4	A5	B1	B2	В3	B4	B5	В6	В7	C1	C2	C3	C4	. D
Х	Х	Х	Х													

# **Environmental impact**

Parameter	Unit	A1	A2	A3	A4
GWP	kg CO <sub>2</sub> -eq	3,66E+01	9,25E-01	1,49E-01	9,19E-02
ODP	kg CFC11 -eq	1,92E-06	1,71E-07	7,29E-09	1,70E-08
POCP	kg C <sub>2</sub> H <sub>4</sub> -eq	1,33E-02	1,51E-04	2,84E-05	1,50E-05
AP	kg SO <sub>2</sub> -eq	1,65E-01	2,95E-03	7,15E-04	2,93E-04
EP	kg PO <sub>4</sub> <sup>3-</sup> -eq	2,96E-02	4,90E-04	9,36E-05	4,86E-05
ADPM	kg Sb -eq	1,94E-04	2,82E-06	2,31E-07	2,80E-07
ADPE	MJ	4,49E+02	1,39E+01	1,65E+00	1,38E+00

GWP Global warming potential; ODP Depletion potential of the stratospheric ozone layer; POCP Formation potential of tropospheric photochemical oxidants; AP Acidification potential of land and water; EP Eutrophication potential; ADPM Abiotic depletion potential for non fossil resources; ADPE Abiotic depletion potential for fossil resources

Reading example: 9.0 E-03 = 9.0\*10-3 = 0.009

\*INA Indicator Not Assessed

#### Resource use

Parameter	Unit	A1	A2	A3	A4
RPEE	MJ	2,25E+02	2,03E-01	1,94E-01	2,02E-02
RPEM	MJ	1,18E+02	0,00E+00	0,00E+00	0,00E+00
TPE	MJ	3,43E+02	2,03E-01	1,94E-01	2,02E-02
NRPE	MJ	5,50E+02	1,43E+01	2,84E+00	1,42E+00
NRPM	MJ	3,36E+01	0,00E+00	0,00E+00	0,00E+00
TRPE	MJ	5,84E+02	1,43E+01	2,84E+00	1,42E+00
SM	kg	1,63E+00	0,00E+00	0,00E+00	0,00E+00
RSF	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00
NRSF	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00
W	m <sup>3</sup>	4,25E-01	2,67E-03	1,36E-03	2,66E-04

RPEE Renewable primary energy resources used as energy carrier; RPEM Renewable primary energy resources used as raw materials; TPE Total use of renewable primary energy resources; NRPE Non renewable primary energy resources used as materials; TRPE Total use of non renewable primary energy resources; SM Use of secondary materials; RSF Use of renewable secondary fuels; NRSF Use of non renewable secondary fuels; NRSF Use of non renewable secondary fuels; W Use of net fresh water

Reading example: 9.0 E-03 = 9.0\*10-3 = 0.009

\*INA Indicator Not Assessed

#### End of life - Waste

Parameter	Unit	A1	A2	A3	A4
HW	kg	1,54E-03	8,33E-06	3,42E-06	8,28E-07
NHW	kg	2,22E+01	7,51E-01	3,46E-02	7,46E-02
RW	kg	INA*	INA*	INA*	INA*

HW Hazardous waste disposed; NHW Non hazardous waste disposed; RW Radioactive waste disposed

Reading example: 9.0 E-03 = 9.0\*10-3 = 0.009

\*INA Indicator Not Assessed

# End of life - Output flow

·					
Parameter	Unit	A1	A2	A3	A4
CR	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00
MR	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00
MER	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00
EEE	MJ	INA*	INA*	INA*	INA*
ETE	MJ	INA*	INA*	INA*	INA*

CR Components for reuse; MR Materials for recycling; MER Materials for energy recovery; EEE Exported electric energy; ETE Exported thermal energy

Reading example: 9.0 E-03 = 9.0\*10-3 = 0.009

\*INA Indicator Not Assessed

# **Additional Norwegian requirements**

#### Greenhouse gas emissions from the use of electricity in the manufacturing phase

National production mix from import, low voltage (production of transmission lines, in addition to direct emissions and losses in grid) of applied electricity for the manufacturing process (A3).

#### **Dangerous substances**

The product contains no substances given by the REACH Candidate list or the Norwegian priority list.

#### Indoor environment

Our furniture doesn't contain any substanses that effect indoor clima

# Additional environmental information

# **Bibliography**

ISO 14025:2010 Environmental labels and declarations - Type III environmental declarations - Principles and procedures.

ISO 14044:2006 Environmental management - Life cycle assessment - Requirements and guidelines.

EN~15804: 2012 + A1: 2013~Environmental~product~declaration-Core~rules~for~the~product~category~of~construction~products.

ISO 21930:2017 Sustainability in buildings and civil engineering works - Core rules for environmental product declarations of construction products.

ecoinvent v3, Allocation, cut-off by classification, Swiss Centre of Life Cycle Inventories.

 $Iversen\ et\ al.,\ (2018)\ eEPD\ v3.0\ -\ Background\ information\ for\ EPD\ generator\ system.\ LCA. no\ report\ number\ 04.18$ 

Vold et al., (2019) EPD generator for Norsk Industri, Background information for industry application and LCA data, LCA.no report number 06.19.

NPCR Part A: Construction products and services. Ver. 1.0. April 2017, EPD-Norge.

NPCR 026 Part B for Furniture. Ver. 2.0 October 2018, EPD-Norge.

epd-norge.no The Norwegian EPD Foundation	<b>Program operator and publisher</b> The Norwegian EPD Foundation Post Box 5250 Majorstuen, 0303 Oslo,Norway	Phone: e-mail: web:	+47 23 08 80 00 post@epd-norge.no www.epd-norge.no
lugos nugos	Owner of the declaration Fora Form AS Mosflatevegen 6154 Ørsta	Phone: e-mail: web:	+47 700 46 000 info@foraform.com www.foraform.no
LCA <sub>no</sub>	<b>Author of the Life Cycle Assessment</b>	Phone:	+47 916 50 916
	LCA.no AS	e-mail:	post@lca.no
	Dokka 1C 1671 Kråkerøy	web:	www.lca.no
LCA,	<b>Developer of EPD generator</b>	Phone:	+47 916 50 916
	LCA.no AS	e-mail:	post@lca.no
	Dokka 1C 1671 Kråkerøy	web:	www.lca.no