

ENVIRONMENTAL PRODUCT DECLARATION

in accordance with ISO 14025, ISO 21930 and EN 15804

Owner of the declaration:	Flokk AS
Program operator:	The Norwegian EPD Foundation
Publisher:	The Norwegian EPD Foundation
Declaration number:	NEPD-3468-2072-EN
Registration number:	NEPD-3468-2072-EN
ECO Platform reference number:	-
Issue date:	26.04.2022
Valid to:	26.04.2027

giroflex 40

Flokk AS

www.epd-norge.no



giroflex
designed to work

General information

Product:

giroflex 40

Owner of the declaration:

Flokk AS
 Contact person: Atle Thiis-Messel
 Phone: 0047 98 25 68 30
 e-mail: atle.messel@flokk.com

Program operator:

The Norwegian EPD Foundation
 Pb. 5250 Majorstuen, 0303 Oslo
 Phone: +47 23 08 80 00
 e-mail: post@epd-norge.no

Manufacturer:

Flokk AS
 Drammensveien 145, 0277 Oslo
 Norway

Declaration number:

NEPD-3468-2072-EN

Place of production:

Flokk - Turek
 ul. Górnicza 8 62-700 Turek
 Poland

ECO Platform reference number:

Management system:

ISO 14001, ISO 9001, ISO 50001(Norway, Sweden)

This declaration is based on Product Category Rules:

CEN Standard EN 15804:2012+A1:2013 serves as core PCR
 NPCR 026:2018 Part B for furniture

Organisation no:

No 928 902 749

Statement of liability:

The owner of the declaration shall be liable for the underlying information and evidence. EPD Norway shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

Issue date:

26.04.2022

Valid to:

26.04.2027

Declared unit:

1 Pcs giroflex 40

Year of study:

2022

Declared unit with option:

A1,A2,A3,A4

Comparability:

EPDs from programmes other than the Norwegian EPD Foundation may not be comparable

Functional unit:

giroflex 40 - 1 pc

Development and verification of EPD:

The declaration has been developed and verified using EPD tool lca.tools ver EPD2020.11, developed by LCA.no AS. The EPD tool is integrated into the company's environmental management system, and has been approved by EPD-Norway

General information on verification of EPD from EPD tools:

Independent verification of data, other environmental information and the declaration according to ISO 14025:2010, § 8.1.3 and § 8.1.4. Individual third party verification of each EPD is not required when the EPD tool is i) integrated into the company's environmental management system, ii) the procedures for use of the EPD tool are approved by EPDNorway, and iii) the process is reviewed annually. See Appendix G of EPD-Norway's General Programme Instructions for further information on EPD tools.

Developer of EPD:

Damian Bakowski

Reviewer of company-specific input data and EPD:

Arleta Derdziak

Verification of EPD tool:

Independent third party verification of the EPD tool, background data and test-EPD in accordance with EPDNorway's procedures and guidelines for verification and approval of EPD tools.

Approved:

Sign

Håkon Hauan, CEO EPD-Norge

Erik Svanes, Norsus AS

(no signature required)

Key environmental indicators	Unit	Cradle to gate A1 - A3
Global warming	kg CO2 eqv	80,16
Total energy use	MJ	1108,48
Amount of recycled materials	%	32.17

Product

Market:

worldwide

Product description:

The giroflex 40 is an elegant, energizing contribution to a work environment, with its health-focused purpose designed with a harmonic approach.

The holistic and timeless design of giroflex 40, is a synergetic combination of the forwarded circular Giroflex-DNA and discreetly placed functional details in its platform and seat, brought to you with outstanding quality that enhance the bloodstream in your body.

The giroflex 40 offers a large variety of functions already included in the standard version and offers an essential range of options and variants for a fast and easy decisionmaking.

Product specification

Please look in additional technical information, page 8.

Technical data:

Seat height loaded: 375-515 mm

Total height (without headrest): 995-1135 mm

Backrest height above seat: 620 mm

Seat width: 510 mm

Backrest width: 445 mm

Total width (5 arm base): 660 mm (diameter 720 mm)

Seat depth: 420-480 mm

Armrest height above seat: 170-260 mm

Seat inclination angle: 0°-3°

Reference service life, product

5 years

Reference service life, building

Materials	kg	%	Recycled share in material (kg)	Recycled share in material (%)
Metal - Aluminium	4,88	23,22	4,76	97,54
Metal - Steel	4,97	23,65	0,68	13,69
Textile - Polyester (PE)	0,35	1,68	0,19	54,55
Plastic - Polyurethane (PUR)	0,85	4,05	0,00	0,00
Plastic - Acrylonitrile butadiene styrene (ABS)	0,01	0,05	0,00	0,00
Plastic - Polypropylene (PP)	4,18	19,88	0,00	0,00
Plastic - Polyoxymethylene (POM)	0,17	0,79	0,00	0,00
Rubber, synthetic	0,02	0,10	0,00	0,00
Packaging - Plastic	0,24	1,14	0,00	0,00
Powder coating	0,01	0,06	0,00	0,00
Plastic - Nylon (PA)	1,34	6,36	0,00	0,00
Plastic - Polyamide with glass fibre (PAGF30)	0,49	2,32	0,00	0,00
Plastic - Polyester	0,01	0,05	0,00	0,00
Total:	17,50		5,63	

LCA: Calculation rules

Declared unit:

1 Pcs giroflex 40

Cut-off criteria:

All major raw materials and all the essential energy is included. The production processes for raw materials and energy flows with very small amounts (less than 1%) are not included. These cut-off criteria do not apply for hazardous materials and substances.


Data quality:

Specific data for the product composition are provided by the manufacturer. They represent the production of the declared product and were collected for EPD development in the year of study. Background data is based on registered EPDs according to EN 15804, Ostfold Research databases, ecoinvent and other LCA databases. The data quality of the raw materials in A1 is presented in the table below.

Allocation:

The allocation is made in accordance with the provisions of EN 15804. Effects of primary production of recycled materials is allocated to the main product in which the material was used. The recycling process and transportation of the material is allocated to this analysis.

System boundary:



Additional technical information:

Mechanism Synchro Move

Girolflex office chairs offer synchro motion, resulting in a natural body movement as you recline in the chair. The more backward you recline the seat, the more your upper body will open up. This movement is created by the synchro mechanism, which drives the motion of the seat and backrest individually, at a ratio of approx. 1:2

Mesh back

Pronounced ergonomic design for optimal adaptation and support. The mesh fabric RUNNER from Camira guarantees optimal comfort and air circulation.

Lumbar support

Height adjustable.

Handles in black plastic, for height adjustment and activation/de-activation of lumbar support function.

Seat with dual-zone profile

The front part (approx. 1/3 of the seat surface) has a 7° forward tilt to relieve pressure on thighs for optimal blood circulation.

Seat-and back frame

Aluminium, polished or powder coated black 810.

Base

5-arm plastic, black 810.

Optional: 5-arm aluminium, polished or powder coated black 810.

Armrest 3D - optional

Height adjustable, with longitudinal and sidewardly slidable armpad.

Headrest - optional

Height adjustable, headrest support aluminium black 810.

Covered by the fabric of seat, when mounted in the fabric of seat.

Optional: mesh RUNNER or Leather NATURA.

Castors

Ø 50 mm black, for hard or soft floors, braked unloaded.

Optional: Ø 65 mm black, for hard or soft floors, braked unloaded.

LCA: Scenarios and additional technical information

The following information describe the scenarios in the different modules of the EPD.

Transport from production place to user (A4)

Type	Capacity utilisation (incl. return) %	Type of vehicle	Distance km	Fuel/Energy consumption	Unit	Value (l/t)
Truck	38,8 %	Truck, 16-32 tonnes, EURO 5	1000	0,044606	l/tkm	44,61
Railway					l/tkm	
Boat					l/tkm	
Other Transportation					l/tkm	

Assembly (A5)

.	Unit	Value
Auxiliary	kg	
Water consumption	m ³	
Electricity consumption	kWh	
Other energy carriers	MJ	
Material loss	kg	
Output materials for waste treatment	kg	
Dust in the air	kg	
VOC emissions	kg	

Use (B1)

.	Unit	Value

Maintenance (B2)/Repair (B3)

.	Unit	Value
Maintenance cycle*		
Auxiliary		
Other resources		
Water consumption	m ³	
Electricity consumption	kWh	
Other energy carriers	MJ	
Material loss	kg	
VOC emissions	kg	

Replacement (B4)/Refurbishment (B5)

.	Unit	Value
Replacement cycle*		
Electricity consumption	kWh	
Replacement of worn parts		
* Described above if relevant		

Operational energy (B6) and water consumption (B7)

.	Unit	Value
Water consumption	m ³	
Electricity consumption	kWh	
Other energy carriers	MJ	
Power output of equipment	kW	

End of Life (C1, C2)

.	Unit	Value
Hazardous waste disposed	kg	
Collected as mixed construction waste	kg	
Reuse	kg	
Recycling		
Energy recovery		
To landfill	kg	

Transport to waste processing (C2)

Type	Capacity utilisation (incl. return) %	Type of vehicle	Distance km	Fuel/Energy consumption	Unit	Value (l/t)
Truck					l/tkm	
Railway					l/tkm	
Boat					l/tkm	
Other Transportation					l/tkm	

LCA: Results

The LCA results are presented below for the declared unit defined on page 2 of the EPD document.

System boundaries (X=included, MND=module not declared, MNR=module not relevant)

Product stage				Construction installation stage	User stage								End of life stage				Beyond the system boundaries
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	Deconstruction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential	
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D	
X	X	X	X	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	

Environmental impact

Parameter	Unit	A1	A2	A3	A4
GWP	kg CO ₂ -eq	7,21E+01	1,94E+00	6,12E+00	2,85E+00
ODP	kg CFC11 -eq	3,18E-06	3,73E-07	1,58E-07	5,25E-07
POCP	kg C ₂ H ₄ -eq	2,00E-02	4,67E-04	1,39E-03	4,64E-04
AP	kg SO ₂ -eq	2,94E-01	1,15E-02	3,68E-02	9,08E-03
EP	kg PO ₄ ³⁻ -eq	4,89E-02	1,44E-03	4,47E-03	1,51E-03
ADPM	kg Sb -eq	2,00E-03	3,81E-06	3,39E-07	8,68E-06
ADPE	MJ	8,07E+02	2,99E+01	6,23E+01	4,29E+01

GWP Global warming potential; ODP Depletion potential of the stratospheric ozone layer; POCP Formation potential of tropospheric photochemical oxidants; AP Acidification potential of land and water; EP Eutrophication potential; ADPM Abiotic depletion potential for non fossil resources; ADPE Abiotic depletion potential for fossil resources

Reading example: 9,0 E-03 = 9,0*10⁻³ = 0,009

*INA Indicator Not Assessed

Resource use

Parameter	Unit	A1	A2	A3	A4
RPEE	MJ	7,33E+01	5,65E-01	7,31E+00	6,25E-01
RPEM	MJ	2,74E-01	0,00E+00	0,00E+00	0,00E+00
TPE	MJ	7,36E+01	5,65E-01	7,31E+00	6,25E-01
NRPE	MJ	9,31E+02	3,09E+01	6,58E+01	4,39E+01
NRPM	MJ	2,63E+02	0,00E+00	0,00E+00	0,00E+00
TRPE	MJ	1,19E+03	3,09E+01	6,58E+01	4,39E+01
SM	kg	5,63E+00	0,00E+00	0,00E+00	0,00E+00
RSF	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00
NRSF	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00
W	m ³	5,88E-01	6,85E-03	3,28E-02	8,22E-03

RPEE Renewable primary energy resources used as energy carrier; RPEM Renewable primary energy resources used as raw materials; TPE Total use of renewable primary energy resources; NRPE Non renewable primary energy resources used as energy carrier; NRPM Non renewable primary energy resources used as materials; TRPE Total use of non renewable primary energy resources; SM Use of secondary materials; RSF Use of renewable secondary fuels; NRSF Use of non renewable secondary fuels; W Use of net fresh water

Reading example: 9,0 E-03 = $9,0 \cdot 10^{-3} = 0,009$

*INA Indicator Not Assessed

End of life - Waste

Parameter	Unit	A1	A2	A3	A4
HW	kg	3,91E-02	1,67E-05	3,14E-02	2,56E-05
NHW	kg	3,40E+01	2,46E+00	2,28E+00	2,31E+00
RW	kg	INA*	INA*	INA*	INA*

HW Hazardous waste disposed; NHW Non hazardous waste disposed; RW Radioactive waste disposed

Reading example: 9,0 E-03 = $9,0 \cdot 10^{-3} = 0,009$

*INA Indicator Not Assessed

End of life - Output flow

Parameter	Unit	A1	A2	A3	A4
CR	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00
MR	kg	0,00E+00	0,00E+00	7,67E-01	0,00E+00
MER	kg	0,00E+00	0,00E+00	4,70E-03	0,00E+00
EEE	MJ	INA*	INA*	INA*	INA*
ETE	MJ	INA*	INA*	INA*	INA*

CR Components for reuse; MR Materials for recycling; MER Materials for energy recovery; EEE Exported electric energy; ETE Exported thermal energy

Reading example: 9,0 E-03 = $9,0 \cdot 10^{-3} = 0,009$

*INA Indicator Not Assessed

Additional Norwegian requirements

Greenhouse gas emissions from the use of electricity in the manufacturing phase

National production mix from import, low voltage (production of transmission lines, in addition to direct emissions and losses in grid) of applied electricity for the manufacturing process (A3).

Electricity mix	Data source	Amount	Unit
Energy, electricity, Poland: 1 kWh	ecoinvent 3.6	1099,70	g CO ₂ -ekv/kWh

Dangerous substances

The product contains no substances given by the REACH Candidate list or the Norwegian priority list.

Indoor environment

Greenguard Gold, Blue Angel

Additional environmental information

Key environmental indicators for variants for this EPD: Cradle to Gate analyse from A1 to A3

Variant number	Global warming (kg CO ₂)	Total energy use (MJ)	Share of recycled material in product(%)
giroflex 40 with ALU starbase polished	80,16	1 108,48	32,17
giroflex 40 with ALU starbase black	80,64	1 117,15	32,12
giroflex 40 with plastic starbase	91,91	1 217,42	24,76

Key environmental indicators for options for this EPD: Cradle to Gate analyse from A1 to A3

Option number	Global warming (kg CO ₂)	Total energy use (MJ)	Share of recycled material in product(%)
giroflex 40 - Armrests polished (set)	40,61	432,86	0,11
giroflex 40 - Armrests black (set)	42,11	448,93	0,11
giroflex 40 - headrest	3,36	50,17	6,31
giroflex 40 - packaging	7,21	83,19	59,40

Bibliography

ISO 14025:2010 Environmental labels and declarations - Type III environmental declarations - Principles and procedures.

ISO 14044:2006 Environmental management - Life cycle assessment - Requirements and guidelines.

EN 15804:2012+A1:2013 Environmental product declaration - Core rules for the product category of construction products.

ISO 21930:2017 Sustainability in buildings and civil engineering works - Core rules for environmental product declarations of construction products.

ecoinvent v3, Allocation, cut-off by classification, Swiss Centre of Life Cycle Inventories.

Iversen et al., (2018) eEPD v3.0 - Background information for EPD generator system. LCA.no report number 04.18

Vold et al., (2019) EPD generator for Norsk Industri, Background information for industry application and LCA data, LCA.no report number 06.19.

NPCR Part A: Construction products and services. Ver. 1.0. April 2017, EPD-Norge.

NPCR 026 Part B for Furniture. Ver. 2.0 October 2018, EPD-Norge.

<p>The Norwegian EPD Foundation</p>	Program operator and publisher The Norwegian EPD Foundation Post Box 5250 Majorstuen, 0303 Oslo, Norway	Phone: +47 23 08 80 00 e-mail: post@epd-norge.no web: www.epd-norge.no
	Owner of the declaration Flokk AS Drammensveien 145, 0277 Oslo	Phone: 0047 98 25 68 30 e-mail: atle.messel@flokk.com web: https://www.flokk.com
	Author of the Life Cycle Assessment LCA.no AS Dokka 1C 1671 Kråkerøy	Phone: +47 916 50 916 e-mail: post@lca.no web: www.lca.no
	Developer of EPD generator LCA.no AS Dokka 1C 1671 Kråkerøy	Phone: +47 916 50 916 e-mail: post@lca.no web: www.lca.no