

ENVIRONMENTAL PRODUCT DECLARATION

in accordance with ISO 14025, ISO 21930 and EN 15804


Owner of the declaration:	Fora Form AS
Program operator:	The Norwegian EPD Foundation
Publisher:	The Norwegian EPD Foundation
Declaration number:	NEPD-3618-2558-EN
Registration number:	NEPD-3618-2558-EN
ECO Platform reference number:	-
Issue date:	06.07.2022
Valid to:	06.07.2027

Kvart table Ø800 RAW

Fora Form AS

www.epd-norge.no

fora
form



Kvart

RAW



Environmental indicators for variants on page 8

General information

Product:

Kvart table Ø800 RAW

Owner of the declaration:

Fora Form AS
 Contact person: Kåre Sætre
 Phone: +47 700 46 000
 e-mail: info@foraform.com

Program operator:

The Norwegian EPD Foundation
 Pb. 5250 Majorstuen, 0303 Oslo
 Phone: +47 23 08 80 00
 e-mail: post@epd-norge.no

Manufacturer:

Fora Form AS

Declaration number:

NEPD-3618-2558-EN

Place of production:

Fora Form AS
 Mosflatevegen 6154 Ørsta
 Norway

ECO Platform reference number:

Management system:

NS-EN ISO 14001: 2015 No. 800406. NS-EN ISO 9001: 2015 No. 901268. NS-EN ISO 45001: 2018 No 907167.

This declaration is based on Product Category Rules:

CEN Standard EN 15804:2012+A1:2013 serves as core PCR
 NPCR 026:2018 Part B for furniture

Organisation no:

986 581 421

Statement of liability:

The owner of the declaration shall be liable for the underlying information and evidence. EPD Norway shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

Issue date:

06.07.2022

Declared unit:

1 Pcs Kvart table Ø800 RAW

Year of study:

2022

Declared unit with option:

A1,A2,A3,A4,A5,B1,B2

Comparability:

EPDs from programmes other than the Norwegian EPD Foundation may not be comparable

Functional unit:

Functional unit whitout cardboard

Development and verification of EPD:

The declaration has been developed and verified using EPD tool lca.tools ver EPD2020.11, developed by LCA.no AS. The EPD tool is integrated into the company's environmental management system, and has been approved by EPD-Norway

General information on verification of EPD from EPD tools:

Independent verification of data, other environmental information and the declaration according to ISO 14025:2010, § 8.1.3 and § 8.1.4. Individual third party verification of each EPD is not required when the EPD tool is i) integrated into the company's environmental management system, ii) the procedures for use of the EPD tool are approved by EPDNorway, and iii) the process is reviewed annually. See Appendix G of EPD-Norway's General Programme Instructions for further information on EPD tools.

Developer of EPD:

Kåre Sætre

Reviewer of company-specific input data and EPD:

Katrine Østgaard

Verification of EPD tool:

Independent third party verification of the EPD tool, background data and test-EPD in accordance with EPDNorway's procedures and guidelines for verification and approval of EPD tools.

Approved:

Sign



Håkon Hauan, CEO EPD-Norge

Erik Svanes, Norsus AS
 (no signature required)

Key environmental indicators	Unit	Cradle to gate A1 - A3
Global warming	kg CO2 eqv	132,13
Total energy use	MJ	1499,33
Amount of recycled materials	%	10,43

Product

Market:

Worldwide

Product description:

Kvart - a timeless and effortless table system.

The base design allows the Kvart series to offer many table types, from smaller project rooms to large canteens or meeting rooms with wider tables. The column of the table has space for cables to ensure a clean and tidy look. Kvart has got its name from the column's profile which indicates four directions. The four lines prolongate into a T and X base and even a H base for extra width.

The RAW table top is made from a selection of surplus material from the wood products industry. And 25 mm. chipboard offers a beautiful and natural game. Through our procedures, we preserve the beautiful expression of the wood and add the quality you are used to on a Fora Form table; completely raw.

Product specification

Furniture test approved :

NS-EN 15372

NS-EN 1730

NS-EN 12720

NS-EN 12722

Technical data:

Weight 13,58 kg (Without cardboard)

Reference service life, product

15 years

Reference service life, building

Materials	kg	%	Recycled share in material (kg)	Recycled share in material (%)
Metal - Aluminium	5,24	33,63	0,05	0,95
Metal - Steel	0,24	1,52	0,05	20,00
Plastic - Polyoxymethylene (POM)	0,00	0,02	0,00	50,00
Wood - Chipboard	8,00	51,35	0,00	0,00
Wood - Solid oak	0,10	0,64	0,00	0,00
Cardboard	2,00	12,84	1,53	76,30
Total:	15,58		1,62	

LCA: Calculation rules

Declared unit:

1 Pcs Kvart table Ø800 RAW

Cut-off criteria:


All major raw materials and all the essential energy is included. The production processes for raw materials and energy flows with very small amounts (less than 1%) are not included. These cut-off criteria do not apply for hazardous materials and substances.

Data quality:

Specific data for the product composition are provided by the manufacturer. They represent the production of the declared product and were collected for EPD development in the year of study. Background data is based on registered EPDs according to EN 15804, Ostfold Research databases, ecoinvent and other LCA databases. The data quality of the raw materials in A1 is presented in the table below.

Materials	Source	Data quality	Year
Metal - Steel	ecoinvent 3.3	Database	2016
Cardboard	ecoinvent 3.4	Database	2017
Metal - Aluminium	ecoinvent 3.4	Database	2017
Metal coating - Powder coating on aluminium	ecoinvent 3.4	Database	2017
Plastic - Polyoxymethylene (POM)	ecoinvent 3.4	Database	2017
Process	ecoinvent 3.4	Database	2017
Wood - Chipboard	ecoinvent 3.4	Database	2017
Wood - Solid oak	ecoinvent 3.6	Database	2019

System boundary:



Additional technical information:

We want you to enjoy your furniture for many years to come. If you follow our advice in this Quality and Maintenance Manual you contribute to prolonged life of your furniture. We only use environmentally friendly materials and processes in our manufacturing unit in Ørsta Norway. Our goal is to manufacture furniture that can last for generations. All furniture made by Fora Form are made of FSC certified wood, manufactured according to ISO 14001, and has an EPD on all products. This ensures sustainability and a “cradle to cradle” philosophy. We actively work to reduce waste. All packing materials and waste are being recycled according to Norsk Gjenvinning.

Norwegian and Swedish Møbelfakta are accredited test facilities where furniture quality, strength, durability, flammability, safety, emissions and materials are tested and documented. A piece of furniture, which lives up to the three areas of requirements of Møbelfakta, has undergone extensive testing, is produced according to ethical guidelines and has been approved according to environmental requirements. Møbelfakta is a guarantee of high quality products. Almost all of Fora Forms collection is Møbelfakta approved.

Fora Form are ISO 9001 quality management, ISO 14001 environmental management and ISO 45001 occupational health and safety management certified. Sustainability is important for Fora Form.

We continuously work to sort and reduce our waste, and collaborate with Norsk Gjenvinning and Grønt Punkt (Green Dot Norway plc) regarding recycling of used packing materials. All wood is FSC certified. Our manufacturing unit in Ørsta use electricity that is 100% originated from renewable sources.

Transportation to an average customer in Oslo is 540 km (A4: average European lorry > 32 tonnes)

LCA: Scenarios and additional technical information

The following information describe the scenarios in the different modules of the EPD.

Transport from production place to user (A4)

Type	Capacity utilisation (incl. return) %	Type of vehicle	Distance km	Fuel/Energy consumption	Unit	Value (l/t)
Truck	38,8 %	Truck, 16-32 tonnes, EURO 5	54	0,044606	l/tkm	2,41
Railway					l/tkm	
Boat					l/tkm	
Other Transportation					l/tkm	

Assembly (A5)

	Unit	Value
Auxiliary	kg	
Water consumption	m ³	
Electricity consumption	kWh	
Other energy carriers	MJ	
Material loss	kg	
Output materials from waste treatment	kg	2,0000
Dust in the air	kg	
VOC emissions	kg	

Use (B1)

	Unit	Value
Water (L)	L/DU	1,00

LCA: Results

The LCA results are presented below for the declared unit defined on page 2 of the EPD document.

System boundaries (X=included, MND=module not declared, MNR=module not relevant)

Product stage			Construction installation stage		User stage							End of life stage				Beyond the system boundaries
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	X	X										

Environmental impact

Parameter	Unit	A1	A2	A3	A4	A5	B1	B2
GWP	kg CO ₂ -eq	1,30E+02	2,22E+00	4,93E-03	1,19E-01	1,07E+00	3,64E-04	0
ODP	kg CFC11 -eq	4,09E-06	4,06E-07	5,14E-10	2,20E-08	1,25E-08	3,50E-11	0
POCP	kg C ₂ H ₄ -eq	4,40E-02	5,57E-04	6,15E-06	1,94E-05	5,80E-05	1,16E-07	0
AP	kg SO ₂ -eq	7,06E-01	1,38E-02	2,93E-05	3,81E-04	5,40E-04	1,90E-06	0
EP	kg PO ₄ ³⁻ -eq	5,78E-02	1,66E-03	8,87E-06	6,31E-05	3,26E-04	2,39E-07	0
ADPM	kg Sb -eq	1,37E-04	5,72E-06	2,29E-08	3,64E-07	1,63E-07	1,33E-09	0
ADPE	MJ	1,17E+03	3,29E+01	5,76E-02	1,80E+00	1,09E+00	4,00E-03	0

GWP Global warming potential; ODP Depletion potential of the stratospheric ozone layer; POCP Formation potential of tropospheric photochemical oxidants; AP Acidification potential of land and water; EP Eutrophication potential; ADPM Abiotic depletion potential for non fossil resources; ADPE Abiotic depletion potential for fossil resources

Reading example: 9,0 E-03 = 9,0*10⁻³ = 0,009

*INA Indicator Not Assessed

Resource use

Parameter	Unit	A1	A2	A3	A4	A5	B1	B2
RPEE	MJ	2,41E+02	5,30E-01	3,77E-01	2,62E-02	1,20E+01	7,60E-04	0
RPEM	MJ	7,57E+01	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0
TPE	MJ	3,17E+02	5,30E-01	3,77E-01	2,62E-02	1,20E+01	7,60E-04	0
NRPE	MJ	1,22E+03	3,38E+01	6,92E-02	1,84E+00	9,08E+00	6,14E-03	0
NRPM	MJ	4,63E-02	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0
TRPE	MJ	1,22E+03	3,38E+01	6,92E-02	1,84E+00	9,08E+00	6,14E-03	0
SM	kg	1,62E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0
RSF	MJ	0,00E+00	0,00E+00	2,66E-05	0,00E+00	0,00E+00	0,00E+00	0
NRSF	MJ	0,00E+00	0,00E+00	2,72E-02	0,00E+00	0,00E+00	0,00E+00	0
W	m ³	6,68E-01	6,06E-03	4,05E-05	3,45E-04	2,91E-03	1,17E-03	0

RPEE Renewable primary energy resources used as energy carrier; RPEM Renewable primary energy resources used as raw materials; TPE Total use of renewable primary energy resources; NRPE Non renewable primary energy resources used as energy carrier; NRPM Non renewable primary energy resources used as materials; TRPE Total use of non renewable primary energy resources; SM Use of secondary materials; RSF Use of renewable secondary fuels; NRSF Use of non renewable secondary fuels; W Use of net fresh water

Reading example: 9,0 E-03 = $9,0 \cdot 10^{-3} = 0,009$

*INA Indicator Not Assessed

End of life - Waste

Parameter	Unit	A1	A2	A3	A4	A5	B1	B2
HW	kg	2,67E-03	1,98E-05	9,12E-08	1,07E-06	2,32E-06	1,58E-08	0
NHW	kg	1,07E+02	1,56E+00	2,83E-03	9,68E-02	7,99E-01	2,30E-04	0
RW	kg	INA*	INA*	INA*	INA*	INA*	INA*	0

HW Hazardous waste disposed; NHW Non hazardous waste disposed; RW Radioactive waste disposed

Reading example: 9,0 E-03 = $9,0 \cdot 10^{-3} = 0,009$

*INA Indicator Not Assessed

End of life - Output flow

Parameter	Unit	A1	A2	A3	A4	A5	B1	B2
CR	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0
MR	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	1,89E-02	0,00E+00	0
MER	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0
EEE	MJ	INA*	INA*	INA*	INA*	INA*	INA*	0
ETE	MJ	INA*	INA*	INA*	INA*	INA*	INA*	0

CR Components for reuse; MR Materials for recycling; MER Materials for energy recovery; EEE Exported electric energy; ETE Exported thermal energy

Reading example: 9,0 E-03 = $9,0 \cdot 10^{-3} = 0,009$

*INA Indicator Not Assessed

Additional Norwegian requirements

Greenhouse gas emissions from the use of electricity in the manufacturing phase

National production mix from import, low voltage (production of transmission lines, in addition to direct emissions and losses in grid) of applied electricity for the manufacturing process (A3).

Electricity mix	Data source	Amount	Unit
Energy, district heating, Norwegian average (kWh)	Østfoldforskning	19,71	g CO2-ekv/kWh

Dangerous substances

The product contains no substances given by the REACH Candidate list or the Norwegian priority list.

Indoor environment

Our furniture doesn't contain any substances that effect indoor clima

Additional environmental information

Key environmental indicators for variants for this EPD: Cradle to Gate analyse from A1 to A3

Variant number	Global warming (kg CO2)	Total energy use (MJ)	Share of recycled material in product(%)
Kvart table Ø1200 RAW	149,11	1 884,46	5,80
Kvart table 2400x800 RAW	225,19	2 850,09	3,88
Kvart table 2400x1200 RAW	244,63	3 314,15	2,84

Bibliography

ISO 14025:2010 Environmental labels and declarations - Type III environmental declarations - Principles and procedures.

ISO 14044:2006 Environmental management - Life cycle assessment - Requirements and guidelines.

EN 15804:2012+A1:2013 Environmental product declaration - Core rules for the product category of construction products.

ISO 21930:2017 Sustainability in buildings and civil engineering works - Core rules for environmental product declarations of construction products.

ecoinvent v3, Allocation, cut-off by classification, Swiss Centre of Life Cycle Inventories.

Iversen et al., (2018) eEPD v3.0 - Background information for EPD generator system. LCA.no report number 04.18

Vold et al., (2019) EPD generator for Norsk Industri, Background information for industry application and LCA data, LCA.no report number 06.19.

NPCR Part A: Construction products and services. Ver. 1.0. April 2017, EPD-Norge.

NPCR 026 Part B for Furniture. Ver. 2.0 October 2018, EPD-Norge.

<p>The Norwegian EPD Foundation</p>	Program operator and publisher The Norwegian EPD Foundation Post Box 5250 Majorstuen, 0303 Oslo, Norway	Phone: +47 23 08 80 00 e-mail: post@epd-norge.no web: www.epd-norge.no
	Owner of the declaration Fora Form AS Mosflåtevegen 6154 Ørsta	Phone: +47 700 46 000 e-mail: info@foraform.com web: www.foraform.no
	Author of the Life Cycle Assessment LCA.no AS Dokka 6B 1671 Kråkerøy	Phone: +47 916 50 916 e-mail: post@lca.no web: www.lca.no
	Developer of EPD generator LCA.no AS Dokka 1C 1671 Kråkerøy	Phone: +47 916 50 916 e-mail: post@lca.no web: www.lca.no