

## ENVIRONMENTAL PRODUCT DECLARATION

in accordance with ISO 14025, ISO 21930 and EN 15804

Owner of the declaration:	Flokk AS
Program operator:	The Norwegian EPD Foundation
Publisher:	The Norwegian EPD Foundation
Declaration number:	NEPD-3715-2659-EN
Registration number:	NEPD-3715-2659-EN
ECO Platform reference number:	-
Issue date:	09.09.2022
Valid to:	09.09.2027

### OFFECCT Thelma, Room divider

Flokk AS



[www.epd-norge.no](http://www.epd-norge.no)



## General information

**Product:**  
OFFECCT Thelma, Room divider

**Owner of the declaration:**  
Flokk AS  
Contact person: Atle Thiis-Messel  
Phone: 0047 98 25 68 30  
e-mail: atle.messel@flokk.com

**Program operator:**  
The Norwegian EPD Foundation  
Pb. 5250 Majorstuen, 0303 Oslo  
Phone: +47 23 08 80 00  
e-mail: [post@epd-norge.no](mailto:post@epd-norge.no)

**Manufacturer:**  
Flokk AS  
Drammensveien 145, 0277 Oslo  
Norway

**Declaration number:**  
NEPD-3715-2659-EN

**Place of production:**  
Flokk - Turek  
ul. Górnicza 8 62-700 Turek  
Poland

**ECO Platform reference number:**

**Management system:**  
ISO 14001, ISO 9001, ISO 50001(Norway, Sweden)

**This declaration is based on Product Category Rules:**  
CEN Standard EN 15804:2012+A1:2013 serves as core PCR  
NPCR 026:2018 Part B for furniture

**Organisation no:**  
No 928 902 749

**Statement of liability:**  
The owner of the declaration shall be liable for the underlying information and evidence. EPD Norway shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

**Issue date:** 09.09.2022

**Valid to:** 09.09.2027

**Declared unit:**  
1 Pcs OFFECCT Thelma, Room divider

**Year of study:**  
2022

**Declared unit with option:**  
A1,A2,A3,A4

**Comparability:**  
EPDs from programmes other than the Norwegian EPD Foundation may not be comparable

**Functional unit:**

**Development and verification of EPD:**  
The declaration has been developed and verified using EPD tool lca.tools ver EPD2020.11, developed by LCA.no AS. The EPD tool is integrated into the company's environmental management system, and has been approved by EPD-Norway

**General information on verification of EPD from EPD tools:**  
Independent verification of data, other environmental information and the declaration according to ISO 14025:2010, § 8.1.3 and § 8.1.4. Individual third party verification of each EPD is not required when the EPD tool is i) integrated into the company's environmental management system, ii) the procedures for use of the EPD tool are approved by EPDNorway, and iii) the process is reviewed annually. See Appendix G of EPD-Norway's General Programme Instructions for further information on EPD tools.

Developer of EPD:  
Damian Bakowski  
Reviewer of company-specific input data and EPD:  
Arleta Derdziak

**Verification of EPD tool:**  
Independent third party verification of the EPD tool, background data and test-EPD in accordance with EPDNorway's procedures and guidelines for verification and approval of EPD tools.

**Approved:**

Erik Svanes, Norsus AS  
(no signature required)

Sign  
  
Håkon Hauan, CEO EPD-Norge

Key environmental indicators	Unit	Cradle to gate A1 - A3
Global warming	kg CO2 eqv	95,96
Total energy use	MJ	1425,62
Amount of recycled materials	%	49,36

## Product

### Market:

Worldwide

### Product description:

The sound absorber Thelma is named after Pauline Deltour's youngest daughter, a name that is said to mean 'divine protection'. "It has a stylized simplicity with fabrics that are wrapped around it and create a tailored and elegant expression. At the same time, I'm struck by the light-hearted playfulness that the sound absorber expresses; it feels self-conscious and urban, but at the same time relaxed and unforced", says Tobias Strålman, Design lead at Offecct.

Since our offices and ways of working have changed, towards increased flexibility and more but smaller spaces for physical and digital meetings. Thelma sound absorber are designed for use in such soft, adaptable work spaces – and also come with smart accessories such as a hook.

### Product specification

Acoustic room divider upholstered in textile.  
Frame, wheel and hook in lacquered metal. Black and white as standard, Flexicolor as an option on request.

### Technical data:

<https://www.offecct.com/product/thelma-room-divider>

### Reference service life, product

5 years

### Reference service life, building

Materials	kg	%	Recycled share in material (kg)	Recycled share in material (%)
Metal - Aluminium	1,65	5,36	1,65	100,00
Metal - Steel	10,41	33,91	1,95	18,72
Textile - Polyester (PE)	3,49	11,36	2,84	81,54
Rubber, synthetic	0,12	0,38	0,00	0,00
Powder coating	0,28	0,91	0,00	0,00
Plastic - Nylon (PA)	0,02	0,06	0,00	0,00
Textile - Felt	4,81	15,67	3,74	77,70
Glue	0,18	0,59	0,01	2,83
Total:	20,95		10,18	

## LCA: Calculation rules

### Declared unit:

1 Pcs OFFECCT Thelma, Room divider

### Cut-off criteria:


All major raw materials and all the essential energy is included. The production processes for raw materials and energy flows with very small amounts (less than 1%) are not included. These cut-off criteria do not apply for hazardous materials and substances.

### Data quality:

Specific data for the product composition are provided by the manufacturer. They represent the production of the declared product and were collected for EPD development in the year of study. Background data is based on registered EPDs according to EN 15804, Ostfold Research databases, ecoinvent and other LCA databases. The data quality of the raw materials in A1 is presented in the table below.

Materials	Source	Data quality	Year
Rubber, synthetic	ecoinvent 3.4	Database	2015
Metal - Steel	ecoinvent 3.3	Database	2016
Metal - Aluminium	ecoinvent 3.4	Database	2017
Metal - Steel	ecoinvent 3.4	Database	2017
Textile - Polyester (PE)	ecoinvent 3.4	Database	2017
Powder coating	ecoinvent 3.5	Database	2018
Plastic - Nylon (PA)	ecoinvent 3.6	Database	2019
Process	ecoinvent 3.6	Database	2019
Textile - Felt	ecoinvent 3.6	Database	2019
Textile - Polyester (PE)	ecoinvent 3.6	Database	2019
Glue	Modified ecoinvent 3.6	Database and supplier	2019

**System boundary:**



**Additional technical information:**

## LCA: Scenarios and additional technical information

The following information describe the scenarios in the different modules of the EPD.

### Transport from production place to user (A4)

Type	Capacity utilisation (incl. return) %	Type of vehicle	Distance km	Fuel/Energy consumption	Unit	Value (l/t)
Truck	38,8 %	Truck, 16-32 tonnes, EURO 5	1000	0,044606	l/tkm	44,61
Railway					l/tkm	
Boat					l/tkm	
Other Transportation					l/tkm	

### Assembly (A5)

	Unit	Value
Auxiliary	kg	
Water consumption	m <sup>3</sup>	
Electricity consumption	kWh	
Other energy carriers	MJ	
Material loss	kg	
Output materials for waste treatment	kg	
Dust in the air	kg	
VOC emissions	kg	

### Use (B1)

	Unit	Value

### Maintenance (B2)/Repair (B3)

	Unit	Value
Maintenance cycle*		
Auxiliary		
Other resources		
Water consumption	m <sup>3</sup>	
Electricity consumption	kWh	
Other energy carriers	MJ	
Material loss	kg	
VOC emissions	kg	

### Replacement (B4)/Refurbishment (B5)

	Unit	Value
Replacement cycle*		
Electricity consumption	kWh	
Replacement of worn parts		

\* Described above if relevant

### Operational energy (B6) and water consumption (B7)

	Unit	Value
Water consumption	m <sup>3</sup>	
Electricity consumption	kWh	
Other energy carriers	MJ	
Power output of equipment	kW	

### End of Life (C1, C2)

	Unit	Value
Hazardous waste disposed	kg	
Collected as mixed construction waste	kg	
Reuse	kg	
Recycling		
Energy recovery		
To landfill	kg	

### Transport to waste processing (C2)

Type	Capacity utilisation (incl. return) %	Type of vehicle	Distance km	Fuel/Energy consumption	Unit	Value (l/t)
Truck					l/tkm	
Railway					l/tkm	
Boat					l/tkm	
Other Transportation					l/tkm	

## LCA: Results

The LCA results are presented below for the declared unit defined on page 2 of the EPD document.

### System boundaries (X=included, MND=module not declared, MNR=module not relevant)

Product stage				Construction installation stage	User stage								End of life stage				Beyond the system boundaries
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	Deconstruction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential	
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D	
X	X	X	X	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	

### Environmental impact

Parameter	Unit	A1	A2	A3	A4
GWP	kg CO <sub>2</sub> -eq	8,76E+01	2,27E+00	6,12E+00	3,36E+00
ODP	kg CFC11 -eq	5,52E-06	4,27E-07	1,58E-07	6,20E-07
POCP	kg C <sub>2</sub> H <sub>4</sub> -eq	2,79E-02	3,68E-04	1,39E-03	5,48E-04
AP	kg SO <sub>2</sub> -eq	3,65E-01	8,66E-03	3,68E-02	1,07E-02
EP	kg PO <sub>4</sub> <sup>3-</sup> -eq	6,43E-02	1,56E-03	4,47E-03	1,78E-03
ADPM	kg Sb -eq	2,62E-03	4,60E-06	3,39E-07	1,02E-05
ADPE	MJ	1,01E+03	3,47E+01	6,23E+01	5,06E+01

GWP Global warming potential; ODP Depletion potential of the stratospheric ozone layer; POCP Formation potential of tropospheric photochemical oxidants; AP Acidification potential of land and water; EP Eutrophication potential; ADPM Abiotic depletion potential for non fossil resources; ADPE Abiotic depletion potential for fossil resources

Reading example: 9,0 E-03 = 9,0\*10<sup>-3</sup> = 0,009

\*INA Indicator Not Assessed

## Resource use

Parameter	Unit	A1	A2	A3	A4
RPEE	MJ	1,22E+02	6,42E-01	7,31E+00	7,38E-01
RPEM	MJ	9,61E-01	0,00E+00	0,00E+00	0,00E+00
TPE	MJ	1,23E+02	6,42E-01	7,31E+00	7,38E-01
NRPE	MJ	1,19E+03	3,58E+01	6,58E+01	5,18E+01
NRPM	MJ	5,77E+01	0,00E+00	0,00E+00	0,00E+00
TRPE	MJ	1,25E+03	3,58E+01	6,58E+01	5,18E+01
SM	kg	1,02E+01	0,00E+00	0,00E+00	0,00E+00
RSF	MJ	2,87E-01	0,00E+00	0,00E+00	0,00E+00
NRSF	MJ	3,04E-01	0,00E+00	0,00E+00	0,00E+00
W	m <sup>3</sup>	9,39E-01	8,42E-03	3,28E-02	9,71E-03

RPEE Renewable primary energy resources used as energy carrier; RPEM Renewable primary energy resources used as raw materials; TPE Total use of renewable primary energy resources; NRPE Non renewable primary energy resources used as energy carrier; NRPM Non renewable primary energy resources used as materials; TRPE Total use of non renewable primary energy resources; SM Use of secondary materials; RSF Use of renewable secondary fuels; NRSF Use of non renewable secondary fuels; W Use of net fresh water

Reading example: 9,0 E-03 =  $9,0 \cdot 10^{-3} = 0,009$

\*INA Indicator Not Assessed

## End of life - Waste

Parameter	Unit	A1	A2	A3	A4
HW	kg	1,32E-01	2,01E-05	3,14E-02	3,03E-05
NHW	kg	5,93E+01	2,91E+00	2,28E+00	2,73E+00
RW	kg	INA*	INA*	INA*	INA*

HW Hazardous waste disposed; NHW Non hazardous waste disposed; RW Radioactive waste disposed

Reading example: 9,0 E-03 =  $9,0 \cdot 10^{-3} = 0,009$

\*INA Indicator Not Assessed

## End of life - Output flow

Parameter	Unit	A1	A2	A3	A4
CR	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00
MR	kg	2,92E-03	0,00E+00	7,67E-01	0,00E+00
MER	kg	1,02E-01	0,00E+00	4,70E-03	0,00E+00
EEE	MJ	INA*	INA*	INA*	INA*
ETE	MJ	INA*	INA*	INA*	INA*

CR Components for reuse; MR Materials for recycling; MER Materials for energy recovery; EEE Exported electric energy; ETE Exported thermal energy

Reading example: 9,0 E-03 =  $9,0 \cdot 10^{-3} = 0,009$

\*INA Indicator Not Assessed

## Additional Norwegian requirements

### Greenhouse gas emissions from the use of electricity in the manufacturing phase

National production mix from import, low voltage (production of transmission lines, in addition to direct emissions and losses in grid) of applied electricity for the manufacturing process (A3).

Electricity mix	Data source	Amount	Unit
Energy, electricity, Poland: 1 kWh	ecoinvent 3.6	1099,70	g CO <sub>2</sub> -ekv/kWh

### Dangerous substances

The product contains no substances given by the REACH Candidate list or the Norwegian priority list.

### Indoor environment

## Additional environmental information

Key environmental indicators for options for this EPD: Cradle to Gate analyse from A1 to A3

Option number	Global warming (kg CO <sub>2</sub> )	Total energy use (MJ)	Share of recycled material in product(%)
OFFECCT Thelma, Hook	0,55	7,71	19,58
OFFECCT Thelma, Packaging	11,07	142,96	96,99

## Bibliography

ISO 14025:2010 Environmental labels and declarations - Type III environmental declarations - Principles and procedures.

ISO 14044:2006 Environmental management - Life cycle assessment - Requirements and guidelines.

EN 15804:2012+A1:2013 Environmental product declaration - Core rules for the product category of construction products.

ISO 21930:2017 Sustainability in buildings and civil engineering works - Core rules for environmental product declarations of construction products.

ecoinvent v3, Allocation, cut-off by classification, Swiss Centre of Life Cycle Inventories.

Iversen et al., (2018) eEPD v3.0 - Background information for EPD generator system. LCA.no report number 04.18

Vold et al., (2019) EPD generator for Norsk Industri, Background information for industry application and LCA data, LCA.no report number 06.19.

NPCR Part A: Construction products and services. Ver. 1.0. April 2017, EPD-Norge.

NPCR 026 Part B for Furniture. Ver. 2.0 October 2018, EPD-Norge.

<p>Global Program Operator</p>	<b>Program operator and publisher</b> The Norwegian EPD Foundation Post Box 5250 Majorstuen, 0303 Oslo, Norway	Phone: +47 23 08 80 00 e-mail: post@epd-norge.no web: www.epd-norge.no
	<b>Owner of the declaration</b> Flokk AS Drammensveien 145, 0277 Oslo	Phone: 0047 98 25 68 30 e-mail: atle.messel@flokk.com web: https://www.flokk.com
	<b>Author of the Life Cycle Assessment</b> LCA.no AS Dokka 6B 1671 Kråkerøy	Phone: +47 916 50 916 e-mail: post@lca.no web: www.lca.no
	<b>Developer of EPD generator</b> LCA.no AS Dokka 1C 1671 Kråkerøy	Phone: +47 916 50 916 e-mail: post@lca.no web: www.lca.no